



## Multiple socket outlets: Multi-outlet 3Schuko+switch 5m white

**00493.X.B**

Portable installation / Plugs and socket outlets / Multiple socket outlets /  
Other multiple socket outlets

**Multi-outlet 3Schuko+switch 5m white**


### Product Status

3 - Active

### Minimum order quantity

10 NR


### Drawings



Space view



Backside view



3D View



## Technical data

- **Class group:** Domestic switching devices
- **Class:** Socket outlet combination
- **Housing shape:** Rectangular
- **Number of socket outlets CEE 7/1 (no protective contact):** 0
- **Number of socket outlets CEE 7/16 (EURO):** 0
- **Number of socket outlets with protective contact CEE 7/3 (type F):** 3
- **Number of socket outlets with earth pin:** 0
- **Number of cold device socket outlets:** 0
- **Number of socket outlets Danish standard (earthing pin):** 0
- **Number of socket outlets French standard type E:** 0
- **Number of socket outlets Italian standard type Bipasso:** 0
- **Number of socket outlets Italian standard type P11:** 0
- **Number of socket outlets Italian standard type P17:** 0
- **Number of NEMA-outlets:** 0
- **Number of socket outlets Swiss standard type 13:** 0
- **Number of socket outlets Swiss standard type 15:** 0
- **Number of socket outlets Swiss standard type 23:** 0
- **Number of socket outlets Swiss standard type 25:** 0
- **With on/off switch:** Yes
- **Residual current circuit breaker (RCCB):** No
- **Number of universal multi standard sockets:** 0
- **Mains filter:** No
- **Number of other socket outlets:** 0
- **Number of USB connections:** 0
- **Over voltage protection:** No
- **Nominal current:** 16 A
- **Core cross section:** 1,50
- **With cover:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** No
- **Anti-bacterial treatment:** No
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** White
- **RAL-number (similar):** 9016
- **Transparent:** No
- **Degree of protection (IP):** IP20
- **Impact strength:** Other
- **Length of power cord:** 5,00 m
- **Rotated central insert:** Yes
- **Angle rotated central insert:** Other
- **NEMA designation:** None
- **Operating temperature:** 0 - 25 °C
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

## Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352725966  
**Quantity** 1 NR  
**Dim.** 27x14x6 [cm]  
**Weight** 729.4 [g]



**Code** 8007352725973  
**Quantity** 10 NR  
**Dim.** 32x26x28 [cm]  
**Weight** 7,794 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).