



Shared components: LED unit 250V 0,35W amber

00936.250.A

Wiring devices / Traditional wiring devices / Shared components /
Accessories

LED unit 250V 0,35W amber

LED signalling unit 250 V 50/60 Hz 0,35 W, amber. With incandescent or halogen lamps, the signalling unit has to be in-line with the charge (indicator unit OFF and controlled lamp ON), with other types of lamps the signalling unit has to be in parallel to the charge (indicator unit On and controlled lamp ON) or connected directly to the main power supply (indicator unit always ON)



Product Status

3 - Active

Minimum order quantity

50 NR

You may also be interested in



00935.A - LED unit 12-24V
0,1W amber

Drawings



Space view



3D View

Technical data

- **Class group:** Domestic switching devices
- **Class:** Illumination insert for domestic switching devices
- **Application:** Switch/push button
- **Lamp type:** LED
- **With light source:** Yes
- **Colour light source:** Amber
- **Lamp holder:** Other
- **Nominal voltage:** 250,00 - 250,01 V

Certifications

- 00. CE Marking - EU
- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 29. QCERT - Colombia
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352562417
Quantity 1 NR
Dim. 0.7x15x0.7 [cm]
Weight 3.94 [g]



Code 8007352562424
Quantity 50 NR
Dim. 13.9x11.9x7.4 [cm]
Weight 238.4 [g]



Code 8007352725065
Quantity 1,000 NR
Dim. 38.5x29.5x25 [cm]
Weight 4,768 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).