



Adaptors: 2P USA adaptor - P10 outlet white

01351.B

Portable installation / Plugs and socket outlets / Adaptors / Residential adaptors

2P USA adaptor - P10 outlet white

125 V \sim SICURY 1-way adaptor, white - max load 1500 W - 2P 15 A 125 V \sim American standard plug with non-polarized flat blades, 2P socket outlet for 2P plugs with Ø 4 mm pins, 19 mm distance between centres

Product Status

3 - Active

Minimum order quantity

100 NR

You may also be interested in





Technical data

Class group: Domestic switching devices

Class: Plug adapter

Model: Single

With plug for AU/NZ/PG/AR (AS/NZS 3112) (type I): No

With plug for BE/DE/NL/RU (protective contact CEE 7/4, type F): No

With plug for FR (earth pin) (type E): No

With plug for UK/HK (BS 1363) (type G): No

With plug for IT (S/P 11): No

With plug for IT (S/P 17) (type L): No

With plug for US/CA/CN (NEMA 1-15) (type A): Yes

With plug for US/CA/CN (NEMA 5-15) (type B): No

Type of bus: IT (S/P 11)
Number of USB ports: 0

Colour: White

Nominal voltage: 230,00 - 230,01 V Nominal current: 0,00 - 10,00 A

Certifications

• 00. CE Marking - EU

10. EAC Eurasian Customs Union

37. Marking - Morocco

- 98. Warning for adapters (download)
- 99. WEEE Directive (download)

Packaging



Code Quantity Dim. Weight

8007352036871 1 NR 3.6x4x1.8 [cm] 12.5 [g]



Code Quantity Dim. Weight

8007352326033 10 NR 20x15x5 [cm] 128.65 [g]



Code Quantity Dim. Weight

8007352008328 100 NR 28.4x18.4x11.6 [cm] 1,397 [g]



Code8007352642713Quantity800 NRDim.59.5x38.5x26.5 [cm]Weight11,896 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.