



# Adaptors: 2P USA adaptor - P10 outlet black

#### 01351

Portable installation / Plugs and socket outlets / Adaptors / Residential adaptors

### 2P USA adaptor - P10 outlet black

125 V~ SICURY 1-way adaptor, black - max load 1500 W - 2P 15 A 125 V~ American standard plug with non-polarized flat blades, 2P socket outlet for 2P plugs with ø 4 mm pins, 19 mm distance between centres

#### **Product Status**

3 - Active

### Minimum order quantity

100 NR

# You may also be interested in





### Technical data

Class group: Domestic switching devices

Class: Plug adapter

Model: Single

With plug for AU/NZ/PG/AR (AS/NZS 3112) (type I): No

With plug for BE/DE/NL/RU (protective contact CEE 7/4, type F): No

With plug for FR (earth pin) (type E): No

With plug for UK/HK (BS 1363) (type G): No

With plug for IT (S/P 11): No

With plug for IT (S/P 17) (type L): No

With plug for US/CA/CN (NEMA 1-15) (type A): Yes

With plug for US/CA/CN (NEMA 5-15) (type B): No

Type of bus: IT (S/P 11) Number of USB ports: 0

Colour: Black

Nominal voltage: 230,00 - 230,01 V Nominal current: 0,00 - 10,00 A

### Certifications

00. CE Marking - EU

10. EAC Eurasian Customs Union

37. Marking - Morocco

- 98. Warning for adapters (download)
- 99. WEEE Directive (download)

## **Packaging**



Code Quantity Dim. Weight

8007352036864 1 NR 3.6x4x1.8 [cm] 12.4 [g]

Code Quantity Dim. Weight

8007352326026 10 NR 20x15x5 [cm] 124.73 [g]



Code Quantity Dim. Weight 1,371.6 [g]

8007352008311 100 NR 28.4x18.4x11.6 [cm]



Code 8007352642720 Quantity 800 NR 59.5x38.5x26.5 [cm] Dim. Weight 11,680 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.