



Shared components: Supply unit 120-230V~ 29Vdc 1280mA

01401

Smart systems&products / By-me Plus / Shared components / DIN devices

Supply unit 120-230V~ 29Vdc 1280mA

Power supply with 29 Vdc 1280 mA output, supply voltage 120-230 V~ 50/60 Hz, with decoupling coil (choke) for DIN (60715 TH35) rail installation, occupies 8 17,5 mm modules

Product Status

3 - Active


Minimum order quantity

1 NR


Sheets, Manuals, Documentation

- [Multilanguage instructions sheet \(963 kb\)](#)


Drawings



Space view



Backside view



3D View



Gallery



Technical data

- **Class group:** Installation bus systems
- **Class:** Power supply for bus system
- **Bus system KNX:** No
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** Yes
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** Other
- **Mounting method:** Other
- **Width in number of modular spacings:** 8
- **With LED indication:** Yes
- **Bus voltage stockable:** No
- **Number of integrated choke coils:** 1
- **Number of lines to feed:** 2
- **Max. output current:** 1.280,00 mA

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352506121
Quantity 1 NR
Dim. 15.8x12.4x9.6 [cm]
Weight 519.1 [g]

Code 8007352573192
Quantity 30 NR
Dim. 59.5x26.5x41.5 [cm]
Weight 16,150 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).