



## Shared components: Toroidal differential current sensor

**01459**

Smart systems&products / By-me Plus / Shared components / Non-modular components

### Toroidal differential current sensor

Toroidal differential current sensor for power actuator, hole diameter 9 mm, cable length 40 cm


### Product Status

3 - Active

### Minimum order quantity

1 NR


### Drawings



Space view



Backside view



3D View



### Technical data

- **Class group:** Installation bus systems
- **Class:** Energy management for bus system
- **Bus system KNX:** No
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** No
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** None
- **Radio frequent bidirectional:** No
- **Model:** Direct/transformer
- **Connection type:** Direct
- **Reactive power:** No
- **Approved according to PTB:** No
- **S0 impulse interface:** None
- **Tariff switch:** No

## Certifications

- 00. CE Marking - EU
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352493247  
**Quantity** 1 NR  
**Dim.** 11x10x1.7 [cm]  
**Weight** 23.5 [g]

**Code** 8007352493254  
**Quantity** 10 NR  
**Dim.** 19x14.3x9.5 [cm]  
**Weight** 288.8 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).