



Surface mounting components: By-alarm - RF magnetic contact+shock whi

01727.1.B

Safety / By-alarm Plus / Surface mounting components / Non-modular components

By-alarm - RF magnetic contact+shock whi

By-alarm detector with magnetic contact for doors and windows with shock sensor, 868 MHz radio frequency connection, 1 input for auxiliary magnetic contact or switch-alarm, powered by 1 lithium 3 V CR123A battery (included), white



Product Status

2 - Will be discontinued

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

- [Multilanguage instructions sheet \(612 kb\)](#)

Technical data

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Opening detector for danger detection system

- **Colour:** White

Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352623392
Quantity 1 NR
Dim. 12.2x7.9x3.3 [cm]
Weight 98.8 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).