



Surface mounting components: By-alarm - RF IR detector

01728

Safety / By-alarm Plus / Surface mounting components / Non-modular components

By-alarm - RF IR detector

By-alarm passive infrared presence detector, 868 MHz radio frequency connection, 1 input for external magnetic contact, powered by one 3 V CR123 battery (supplied)

Product Status

2 - Will be discontinued

Minimum order quantity


1 NR

Sheets, Manuals, Documentation


- [Multilanguage instructions sheet \(1002 kb\)](#)
- [Anweisungsblatt \(626 kb\)](#)




Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Alarm installations, emergency call and signalling
- **Class:** Movement detector for danger detection system
- **Type of messaging:** Passive infrared
- **Mounting method:** Surface mounting
- **Detection range:** 98
- **Operating current:** 0,00 mA
- **Operating voltage:** 3,00 - 3,01 V
- **Height:** 111,00 mm
- **Width:** 60,80 mm
- **Depth:** 45,40 mm
- **Characteristic:** Distance
- **Cover monitoring:** Yes
- **Radio system:** Yes

Certifications

- 00. CE Marking - EU
- 19. NOM - Mexico
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352548022
Quantity 1 NR
Dim. 14.2x6.7x5.9 [cm]
Weight 136 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).