



## Shared components: Supply unit from 12-24V to 29V

### 01970

Smart systems&products / By-me Plus / Shared components / DIN devices

### Supply unit from 12-24V to 29V

Power supply with 29 V d.c. 800 mA output, supply voltage 12-24 V~ 50-60 Hz or 12-24 V d.c. (SELV), with decoupling coil, for EN 50022 rail installation, occupies 9 17,5 mm modules. For nautical scope



### Product Status

3 - Active

### Minimum order quantity

1 NR

### Sheets, Manuals, Documentation

- [Documento pdf B.C08014 \(9425 kb\)](#)
- [Instructions sheet \(143 kb\)](#)

### Technical data

- **Class group:** Installation bus systems
- **Class:** Power supply for bus system
- **Bus system KNX:** Yes
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** Yes
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** Other
- **Mounting method:** DRA (DIN-rail adapter)
- **Width in number of modular spacings:** 9
- **With LED indication:** No
- **Bus voltage stockable:** No
- **Number of lines to feed:** 2
- **Max. output current:** 800,00 mA

### Certifications

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352347342  
**Quantity** 1 NR  
**Dim.** 27.6x16.9x11.1 [cm]  
**Weight** 655.8 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).