



8000: TV-RD-SAT single conn.male outlet 1dB

08190.01

Wiring devices / Traditional wiring devices / 8000 / Devices

TV-RD-SAT single conn.male outlet 1dB

Coaxial TV-RD-SAT 5-2400 MHz socket outlet single connection, with IEC 60169-2 male connector, connection attenuation 1 dB. Allows the passage of d.c. current and control signals (24 V 500 mA max).


Product Status

3 - Active


Minimum order quantity

20 NR


Drawings



Space view



Backside view



3D View



Technical data

- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** End socket
- **Cover:** None
- **Tap loss at 860 MHz:** 0,10 dB
- **Tap loss at 2150 MHz:** 0,20 dB
- **Number of outlets:** 1
- **Suitable for remote power supply:** Yes
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** Beige
- **RAL-number (similar):** 9001
- **Material:** Plastic

Certifications


- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

Packaging



8 007352 100992

Code 8007352100992
Quantity 1 NR
Dim. 4.1x2.8x5.3 [cm]
Weight 39.9 [g]



8 007352 101005

Code 8007352101005
Quantity 20 NR
Dim. 21.4x11.6x6 [cm]
Weight 862.8 [g]



8 007352 641495

Code 8007352641495
Quantity 200 NR
Dim. 30.5x25.5x22.5 [cm]
Weight 9,260 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).