8000: 2P 10AX 2-way switch

08286

Wiring devices / Traditional wiring devices / 8000 / Devices

2P 10AX 2-way switch

2P 10 AX 250 V~ 2-way switch (6 terminals), with directional arrows and central OFF position. Max 100 W for self-ballasted lamps (IEC 60669-1:2017)

Product Status

3 - Active

Minimum order quantity

50 NR

Technical data

- **Class group**: Domestic switching devices
- **Class**: Push button
- **Assembly arrangement**: Modular device for domestic switching devices
- **Model**: Other
- **Method of operation**: Rocker
- **Number of rockers**: 1
- **Number of poles**: 2
- **Nominal voltage**: 250 V
- **Rated current**: 10,00 A
- **With lighting**: No
- **Feedback-signal contact**: No
- **Mounting method**: Flush-mounted
- **Type of fastening**: Engage (snap)
- **Material**: Plastic
- **Material quality**: Thermoplastic
- **Halogen free**: Yes
- **Surface protection**: Untreated
- **Surface finishing**: Matt
- **Colour**: White
- **RAL-number (similar)**: 9001
- **Transparent**: No
- **Label space/information surface**: Yes
- **Suitable for degree of protection (IP)**: IP40
- **Device height**: 45,00 mm
- **Device depth**: 43,00 mm

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy (download)
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert (download)
- 99. WEEE Directive (download)

Packaging

Code	8007352014527
Quantity	1 NR
Dim.	5.1x2.8x5.3 [cm]
Weight	37.82 [g]

Code	8007352009271
Quantity	50 NR
Dim.	26.9x11.6x14.2 [cm]
Weight	2,014.2 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.