



## 8000: 1P 10AX 1-way switch +key

#### 08384

Wiring devices / Traditional wiring devices / 8000 / Devices

**1P 10AX 1-way switch +key** 1P NO + 1P NC 10 AX 250 V~ key-operated 1-way switch

#### **Product Status**

2 - Will be discontinued

### Minimum order quantity

20 NR

### Technical data

- Class group: Domestic switching devices
- Class: Installation switch
- Wiring system: Off switch 1-pole
- Method of operation: Key
- Assembly arrangement: Modular device for domestic switching devices
- Number of modules (module system): 1
- Push button switch: Yes
- Number of rockers: 0
- Mounting method: Flush-mounted
- Type of fastening: Engage (snap)
- With mounting plate: No
- Material: Plastic
- Material quality: Thermoplastic
- Halogen free: Yes
- Surface protection: Untreated
- Surface finishing: Matt



- **Colour**: Beige
- RAL-number (similar): 9001
- Label space/information surface: Yes
- Illumination: No
- **Function lighting**: Other
- Type of lighting: Other
- Suitable for degree of protection (IP): IP40
- Nominal voltage: 250 V
- Rated current: 10,00 A
- Feedback-signal contact: No
- **Connection type**: Screwed terminal
- Washing machine switch: No
- Device height: 45,00 mm
- Device depth: 43,00 mm
- Built-in depth: 33,50 mm

## Certifications

- 00. CE Marking EU
- 01. IMQ Italy (download)
- 14. TSE Turkey

# Packaging





 Code
 8007352014886

 Quantity
 1 NR

 Dim.
 6x2.8x5.3 [cm]

 Weight
 48.73 [g]

 Code
 80

 Quantity
 20

 Dim.
 28

 Weight
 1,

8007352016897 20 NR 28.1x13.1x6 [cm] 1,056.07 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

### 37. Marking - Morocco

- 43. UKCA mark Great Britain
- 96. Electrotechnical expert (download)