



8000: 2P+E 16A French out. alum.snapfix black

08615.N

Wiring devices / Traditional wiring devices / 8000 / Devices

2P+E 16A French out. alum.snapfix black

2P+E 16 A 250 V~ SICURY socket outlet, French standard - provided with mounting frame and anodized aluminium cover plate for round mounting boxes, snap fixing, black



Product Status

3 - Active

Minimum order quantity

10 NR

Technical data

- Class group: Domestic switching devices
- Class: Socket outlet
- Number of socket outlets switchable: 0
- Imprint/indication: None
- **Connection type**: Screwed terminal
- With hinged lid: No
- With enhanced contact protection: Yes
- Label space/information surface: Yes
- **Colour**: White
- RAL-number (similar): 9001
- Metallic colour: NoTransparent: NoLockable: No
- Eject-mechanism: No
 Insulated mounting: No
- With function lighting: No
- Over voltage protection: No

- Fault current protection: No
- Mounting method: Flush-mounted
- **Material**: Plastic
- Material quality: Thermoplastic
- Halogen free: Yes
- Surface protection: Untreated
- Surface finishing: Matt
- With loop through function: No
- With on/off switch: No
- Rotated central insert: No
- Nominal current: 16 A
- Nominal voltage: 250 V
- Frequency: 50,00 60,00 HZ
- Suitable for degree of protection (IP): IP20
- Impact strength: Other
- Device height: 45,00 mm

Certifications

- 00. CE Marking EU
- 04. NF France (download)

- 37. Marking Morocco
- 99. WEEE Directive (download)

Packaging



8007352042094

 Quantity
 1 NR

 Dim.
 8.5x8.5x4 [cm]

 Weight
 71.5 [g]



Code 8007352017702 **Quantity** 10 NR

Dim. 26.9x11.6x9 [cm]

Weight 715 [g]

Legal

Code

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.