



NEVE UP: IoT connected radar sensor 1M white

09179

Wiring devices / View Wireless wiring devices / NEVE UP / Devices

IoT connected radar sensor 1M white

Product Status

3 - Active

Minimum order quantity


1 NR




Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(1270 kb\)](#)
- [Full \(1182 kb\)](#)
- [Foglio istruzioni Full \(1140 kb\)](#)
- [Notice technique Full \(1105 kb\)](#)
- [Ficha de instrucciones Full \(1134 kb\)](#)
- [Full instructions sheet \(1131 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(1254 kb\)](#)
- [Anweisungsblatt Full \(1104 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)


Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Domestic switching devices
- **Class:** Movement sensor/presence detector complete
- **Model:** Movement sensor
- **Sensor type:** High frequency
- **With DALI interface:** No
- **Constant light control:** No
- **HVAC-control:** No
- **Forced switch on:** Yes
- **Forced switch off:** No
- **Animal zone:** Yes
- **Creep-under protection:** No
- **Networkable:** Yes
- **Scan angle:** 100
- **Optimum mounting height:** 1,00 m
- **Staircase light controller:** No
- **Bridging switch:** No
- **Max. reach sideways:** 7 m
- **Max. presence range:** 45 m²
- **Max. reach frontally:** 7 m
- **Diameter reach on floor:** 0 m
- **Suitable for wireless transmission:** Yes
- **Remote operation:** Yes
- **With remote control:** No
- **Response value sensitivity adjustable:** Yes
- **Response value luminosity adjustable:** No
- **With signal unit:** Yes
- **Teach-function for response value luminosity:** No
- **Dim function with dimmer basic element:** No
- **Mounting method:** Flush-mounted
- **Suitable for ceiling mounting:** No
- **Connection type:** Screwed terminal
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Anti-bacterial treatment:** No
- **Colour:** White
- **RAL-number (similar):** 9003
- **Transparent:** No
- **Degree of protection (IP):** IP40
- **Voltage type:** AC
- **Frequency:** 50 - 60 HZ
- **Min. switch-on time:** 70 s
- **Max. duty cycle:** 0 min
- **Switch-off delay:** 1.080 s
- **Switching-on delay:** 0 s
- **Detection angle horizontal:** 0 - 100
- **Max. switching power:** 12,00 W
- **Max. switching power LED:** 12 W
- **Suitable for C-load:** No
- **Temperature:** 10 - 40 °C
- **Number of switching zones:** 1
- **Max. starting current:** 0,00 A
- **Min. starting current:** 0 A
- **Control current:** 0 mA
- **Substation input:** No
- **With alarm function:** Yes
- **Width:** 22,30 mm
- **Height:** 47,00 mm
- **Depth:** 49,40 mm
- **Built-in width:** 22,30 mm
- **Built-in depth:** 39,90 mm
- **Built-in length:** 47,00 mm
- **Min. depth of built-in installation box:** 48 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 40. Bluetooth technology
- 43. UKCA mark - Great Britain
- 46. UK PSTI compliance ([download](#))
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352732629
Quantity 1 NR
Dim. 5.2x3.5x5.3 [cm]
Weight 47 [g]

Code 8007352732636
Quantity 10 NR
Dim. 19x11.3x6.2 [cm]
Weight 528.4 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).