



Connector block boxes: Surface-box 3M 40mm depth ivory

09973.A

System infrastructure / Enclosures and control units / Connector block boxes / Surface mounting

Surface-box 3M 40mm depth ivory

3-module surface mounting box, 40 mm depth, for 8000, Linea and 7000 with relevants mounting frame, cover plates or self-bearing cover plates, RAL 9001 ivory. Not suitable for 08065..., 08081..., 08341, 08342, 08440, 08441, 08443, 08445, 08446, 08450, 08470, 08480, 08481, 10064..., 10065..., 10081.... To be installed on insulating non-perforated or metallic with earth connection surfaces.




Product Status

3 - Active

Minimum order quantity

20 NR

Drawings



Space view







3D View

Technical data

- Class group: Connection material (electrotechnical)
- Class: Box/housing for surface mounting on the wall/ceiling
- Max. conductor cross section: 0
- Equipped with: None
- Shape: Rectangular
- Mounting method: Wall-/ceiling mounting
- Mounting in the soil: No
- Mounting under water: No
- For tube diameter: 20/25 mm
- Inlet from the rear: Yes
- Length: 80,00 mm
- Width: 124,00 mm
- Depth: 40,00 mm
- Diameter: 0 mm
- Tackable: No
- Number of inlets: 4
- Type of housing feed-through: None
- Material: Plastic

Certifications

- 01. IMQ Italy
- 37. Marking Morocco

Packaging



Code	8007352043855
Quantity	1 NR
Dim.	12x8x4 [cm]
Weight	53.27 [g]



Dim. Weight

8007352003439 Quantity 20 NR 28.4x24.4x17.9 [cm] 1,287.73 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Halogen free: Yes
- Surface protection: Untreated
- **Colour**: White
- Degree of protection (IP): IP20
- Cover model: Other
- Transparent cover: No
- Cover attachment: Screwed
- Castable: No
- With casting compound: No
- Sealable: No
- Rated insulation voltage Ui: 450 V
- Circuit integrity: None
- With screening: No
- Weatherproof: No
- Operating temperature: 0 60 °C
- Explosion-tested version: No
- For Ex-zone gas: None
- For Ex-Zone dust: None
- 96. Electrotechnical expert (download)