



Connector block boxes: Surface-box 3M 43,5mm depth white

09975.01

System infrastructure / Enclosures and control units / Connector block boxes / Surface mounting

Surface-box 3M 43,5mm depth white

3-module surface mounting box, 43,5 mm depth, for Eikon, Idea and Plana with relevants mounting frame and cover plates, white. To be installed on insulating non-perforated or metallic with earth connection surfaces. Idea: suitable only for Classica cover plates




Product Status

3 - Active

Minimum order quantity

20 NR

Drawings







Backside view



3D View

Gallery





Technical data

Class group: Connection material (electrotechnical)

Class: Box/housing for surface mounting on the wall/ceiling

Max. conductor cross section: 0

• Equipped with: None • Shape: Rectangular

Mounting method: Wall-/ceiling mounting

Mounting in the soil: NoMounting under water: NoFor tube diameter: 20/25 mm

Inlet from the rear: Yes
Length: 84,00 mm
Width: 121,50 mm
Depth: 45,00 mm
Diameter: 0 mm

Tackable: No

Number of inlets: 4

Type of housing feed-through: None

Material: Plastic

Halogen free: Yes

Surface protection: Untreated

Colour: White

Degree of protection (IP): IP20

Cover model: Other
Transparent cover: No
Cover attachment: Screwed

Castable: No

With casting compound: No

Sealable: No

Rated insulation voltage Ui: 450 V

Circuit integrity: NoneWith screening: NoWeatherproof: No

Operating temperature: 0 - 60 °C Explosion-tested version: No

For Ex-Zone gas: None
For Ex-Zone dust: None

Certifications

00. CE Marking - EU

• 01. IMQ - Italy (download)

• 37. Marking - Morocco

43. UKCA mark - Great Britain

96. Electrotechnical expert (download)

Packaging



Code Quantity Dim.

8007352130258 1 NR 12.2x8.4x4.5 [cm]

60.74 [g]

Code Quantity

20 NR 28.4x24.4x17.9 [cm] Dim. Weight 1,428.6 [g]

8007352130265

Code 8007352470644 Quantity 80 NR

59.5x38.5x26.5 [cm] Dim. Weight 6,434.4 [g]

Legal

Weight

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.