

09976.14

System infrastructure / Enclosures and control units / Connector block boxes / Surface mounting

Surface-box 3M 30mm depth Idea grey


3-module surface mounting box, 30 mm depth, for Eikon, Idea and Plana devices with relevants mounting frame and cover plates, Idea grey. To be installed on insulating non-perforated or metallic with earth connection surfaces. Idea series: suitable only for Classica cover plates. Eikon series: suitable only for Eikon Chrome cover plates

Product Status

3 - Active

Minimum order quantity 5 NR

Drawings



Space view



Backside view





3D View





Technical data

- Class group: Connection material (electrotechnical)
- Class: Box/housing for surface mounting on the wall/ceiling
- Max. conductor cross section: 0
- Equipped with: None
- Shape: Rectangular
- Mounting method: Wall-/ceiling mounting
- Mounting in the soil: No
- Mounting under water: No
- For tube diameter: 20/25 mm
- Inlet from the rear: Yes
- Length: 84,00 mm
- Width: 121,50 mm
- Depth: 30,00 mm
- Diameter: 0 mm
- Tackable: No
- Number of inlets: 4
- Type of housing feed-through: None
- Material: Plastic

Certifications

- 00. CE Marking EU
- 01. IMQ Italy (download)
- 37. Marking Morocco

Packaging



Code	8007352138971
Quantity	1 NR
Dim.	12.1x8.4x3 [cm]
Weight	34.67 [g]





8007352138988 Quantity 5 NR 19x14.3x9.5 [cm] Weight 194.61 [g]

Code

Dim.

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Halogen free: Yes
- Surface protection: Untreated
- Colour: Grey
- Degree of protection (IP): IP20
- Cover model: Other
- Transparent cover: No
- Cover attachment: Screwed
- Castable: No
- With casting compound: No
- Sealable: No
- Rated insulation voltage Ui: 450 V
- Circuit integrity: None
- With screening: No
- Weatherproof: No
- Operating temperature: 0 60 °C
- Explosion-tested version: No
- For Ex-zone gas: None
- For Ex-Zone dust: None
- 43. UKCA mark Great Britain
- 96. Electrotechnical expert (download)