



ARKÉ: Zigbee2-way switch kit ArkéClassic white

0K19592.01

Wiring devices / View Wireless wiring devices / ARKÉ / Devices

Zigbee2-way switch kit ArkéClassic white

View Wireless connected 2-way switch kit with: 1 19592.0 2-way switch mechanism, 1 19022.B interchangeable 2-module button white, 1 19607 2-module British standard mounting frame, 1 19603 2-module mounting frame without screws, 1 19642.74 2-module Arké Classic cover plate white

- The smart switch allows to control lamps, or other kind of loads, either using a voice command or an app for smartphone/tablet or pressing the push button
- The smart switch can be controlled through a wireless connection by a Zigbee 3.0 smart home hub, such as Amazon Echo Plus, Echo Show or Echo Studio
- Amazon Alexa voice assistant is able to discover easily the smart switch and add it to the list of its own devices
- The smart switch can be installed in existing electrical systems with wired multi-way and two-way switches
- The smart switch works in the range of 100-240V 50/60Hz and the relay output is suitable for incandescent lamps up to 500W, LED lamps up to 100W, electronic transformers up to 250VA, fluorescent lamps up to 120W
- The timed switch-off and the power-on duration can be configured using the on-board push button
- The smart switch has a wired input that allows other traditional push buttons to control the smart switch
- The smart switch performs the automatic opening of the relay for thermal protection
- The smart switch must be powered with the same phase (L) and neutral (N) that power the load. In installation with wired multi-way and two-way switches, the smart switch should be always powered, therefore it should be installed instead of the wired two-way switch furthest from the load
- The smart switch is provided with two frames for French/German and British international standards
- For flush-mounting installation, it needs at least 5 cm deep backplate
- Compatible with SmartThings hub



Product Status

Kit components







19022.B - Button 2M white



19607 - Frame 2M BS



19603 - Frame 2M without screws 71mm



19642.74 - Classic plate 2M technopolymer white

Sheets, Manuals, Documentation

- Manuale app View Wireless (15556 kb)
- Manuel appli View Wireless (37703 kb)
- Manual app View Wireless (37528 kb)
- Manual View Wireless app (37579 kb)
- Εγχειρίδιο τεχνικού εγκατάστασης (37781 kb)
- Installationsanleitung View Wireless (37508 kb)

Gallery



Technical data

Class group: Domestic switching devices

Class: Installation switch

Wiring system: Two-way switch

Method of operation: Rocker/button

Assembly arrangement: Modular device for domestic switching devices

Number of modules (module system): 1

Push button switch: Yes Number of rockers: 1

Mounting method: Flush-mounted Type of fastening: Engage (snap)

With mounting plate: No

Material: Plastic

Material quality: Thermoplastic Surface protection: Untreated

Surface finishing: Matt

Colour: White

RAL-number (similar): 9016

Label space/information surface: Yes

Illumination: Optional

Function lighting: Illuminated (on) Type of lighting: LED not exchangeable Connection type: Screwed terminal

Washing machine switch: No

Device width: 22,20 mm Device height: 49,00 mm Device depth: 48,60 mm Built-in depth: 36,50 mm

Certifications

00. CE Marking - EU

43. UKCA mark - Great Britain

99. WEEE Directive (download)

Packaging



8007352646681 Code

Quantity 1 NR Dim.

14.2x9.8x9.1 [cm]

Weight 176.8 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.