



## LINEA Classica: 2P 16AX 1-way switch

**10016**

Wiring devices / Traditional wiring devices / LINEA Classica / Devices

### 2P 16AX 1-way switch

2P 16 AX 250 V~ 1-way switch. Max 200 W for self-ballasted lamps (IEC 60669-1:2017)

### Product Status

3 - Active

### Minimum order quantity

50 NR

## Technical data

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** 2-pole switch
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Push button switch:** Yes
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Beige
- **RAL-number (similar):** 9001
- **Label space/information surface:** Yes
- **Nominal voltage:** 250 V
- **Rated current:** 16,00 A
- **Feedback-signal contact:** No
- **Washing machine switch:** Yes
- **Device width:** 22,00 mm
- **Device height:** 36,00 mm
- **Device depth:** 35,50 mm
- **Built-in depth:** 23,50 mm



## Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey ([download](#))
- 19. NOM - Mexico
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352020047  
**Quantity** 1 NR  
**Dim.** 4.1x2.8x5.3 [cm]  
**Weight** 28.13 [g]

**Code** 8007352010093  
**Quantity** 50 NR  
**Dim.** 21.4x11.6x14.2 [cm]  
**Weight** 1,494.13 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).