PLANA: 1P 10AX 2-way switch mechanism

14004.0

Wiring devices / Traditional wiring devices / PLANA / Devices

1P 10AX 2-way switch mechanism

1P 10 AX 250 V~ 2-way switch mechanism, lightable, to complete with 1,2 or 3-module button. Max 100 W for self-ballasted lamps (IEC 60669-1:2017)

Product Status

3 - Active

Minimum order quantity

50 NR

You may also be interested in

14021 - Button 1M lightable ring pilot white

14021.C - Button 1M bell symbol white

14021.C.SL - Button 1M bell symbol Silver

14021.G - Button 1M lightable disc pilot white

14021.G.SL - Button 1M customizable Silver

14021.L - Button 1M light symbol white

14021.L.SL - Button 1M light symbol Silver

14021.P - Button 1M key symbol white

14021.P.SL - Button 1M key symbol Silver

14021.PS - Button 1M PRESS white

14021.PS.SL - Button 1M PRESS Silver

14021.SL - Button 1M lightable Silver

14022 - Button 2M lightable ring pilot white

14022.AB - Antibacterial Button 2M lightable

14022.C - Button 2M bell symbol white

14022.C.SL - Button 2M bell symbol Silver

14022.G - Button 2M lightable disc pilot white

14022.G.SL - Button 2M customizable Silver

14022.L - Button 2M light symbol white

14022.L.SL - Button 2M light symbol Silver

14022.P - Button 2M key symbol white

14022.P.SL - Button 2M key symbol Silver

14022.PS - Button 2M PRESS white

14022.PS.SL - Button 2M PRESS Silver

14022.SL - Button 2M lightable Silver

14023 - Button 3M lightable ring pilot white

14023.C - Button 3M bell symbol white

14023.C.SL - Button 3M bell symbol Silver

14023.G - Button 3M lightable disc pilot white

14023.G.SL - Button 3M customizable Silver

14023.SL - Button 3M lightable Silver

00931 - Pre-wired LED unit 110-250V 0,5W amber

00935.A - LED unit 12-24V 0,1W amber

00935.B - LED unit 12-24V 0,1W light blue

00935.G - LED unit 12-24V 0,1W green

00935.R - LED unit 12-24V 0,1W red

00935.W - LED unit 12-24V 0,1W white

00936.250.A - LED unit 250V 0,35W amber

00936.250.B - LED unit 250V 0,35W light blue

00936.250.G - LED unit 250V 0,35W green

00936.250.R - LED unit 250V 0,35W red

00936.250.W - LED unit 250V 0,35W white

Drawings



Space view



Backside view



3D View

Technical data

- **Class group**: Domestic switching devices
- **Class**: Installation switch
- **Wiring system**: Two-way switch
- **Method of operation**: Rocker/button
- **Assembly arrangement**: Modular device for domestic switching devices
- **Number of modules (module system)**: 1
- **Push button switch**: Yes
- **Number of rockers**: 1
- **Mounting method**: Flush-mounted
- **Type of fastening**: Engage (snap)
- **With mounting plate**: No
- **Material**: Plastic
- **Material quality**: Thermoplastic
- **Halogen free**: Yes
- **Surface protection**: Untreated
- **Surface finishing**: Glossy
- **Colour**: Green
- **RAL-number (similar)**: 9003
- **Label space/information surface**: Yes
- **Illumination**: Optional
- **Function lighting**: Control and orientation
- **Type of lighting**: LED exchangeable
- **Suitable for degree of protection (IP)**: IP40
- **Nominal voltage**: 250 V
- **Rated current**: 10,00 A
- **Feedback-signal contact**: No
- **Connection type**: Screwed terminal
- **Washing machine switch**: No
- **Device width**: 22,30 mm
- **Device height**: 49,00 mm
- **Device depth**: 38,40 mm
- **Built-in depth**: 24,00 mm

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy (download)
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey
- 15. CCC - China (download)
- 19. NOM - Mexico
- 20. IQC - Argentina
- 28. NSW - Australia (download)
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert (download)
- 99. WEEE Directive (download)

Packaging



Code	8007352106420
Quantity	1 NR
Dim.	4.1x2.8x5.3 [cm]
Weight	25.4 [g]

Code	8007352118690
Quantity	50 NR
Dim.	21.6x11.6x14.3 [cm]
Weight	1,363.6 [g]

Code	8007352641006
Quantity	500 NR
Dim.	57.5x22.5x30 [cm]
Weight	14,120 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.