



PLANA: IR receiver+dimmer 230V Silver

14175.SL

Wiring devices / Traditional wiring devices / PLANA / Devices

IR receiver+dimmer 230V Silver

Infrared receiver with dimmer, supply voltage 230 V~ 50 Hz for: 40-450 W incandescent lamps, 40-450 VA ferromagnetic transfomers and 40-300 VA inductive response electronic transformers, control and regulation with built-in push button, 01849 remote control or from NO peripheral push buttons, MASTER function, MOSFET+TRIAC technology, visible in darkness, Silver

Product Status

2 - Will be discontinued


Minimum order quantity

5 NR

Sheets, Manuals, Documentation

• Multilanguage instructions sheet (493 kb)


Drawings



Space view



Backside view



3D View



Technical data

- Class group: Domestic switching devices
- **Class**: Dimmer
- Method of operation: Infrared
- Type of load: Inductive load
- Applicable with button: Yes
- Applicable with movement sensor: No
- Applicable with presence indicator: No
- Applicable with time switch/timer: No
- Applicable with transmission button: No
- Applicable with infrared button: Yes
- Mounting method: Flush-mounted
- Type of fastening: Snapper mounting
- Material: Plastic

Certifications

- 00. CE Marking EU
- 37. Marking Morocco

Packaging



Code	8007352311220
Quantity	1 NR
Dim.	5.1x4.3x5.3 [cm]
Weight	54.64 [g]

 Code
 80

 Quantity
 5

 Dim.
 14

 Weight
 32

8007352311237 5 NR 14.4x11.6x6 [cm] 327.53 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Material quality: Thermoplastic
- Surface protection: Lacquered
- **Surface finishing**: Glossy
- Colour: Silver
- RAL-number (similar): 9006
- Transparent: No
- Suitable for degree of protection (IP): IP40
- Nominal voltage: 230,00 230,01 V
- Frequency: 50,00 50,01 HZ
- **Control voltage**: 230,00 230,01 V
- Device width: 22,30 mm
- Device height: 49,00 mm
- Device depth: 51,00 mm
- 96. Electrotechnical expert (download)
- 99. WEEE Directive (download)