



## PLANA: Emergency lighting device 120V

14393

Wiring devices / Traditional wiring devices / PLANA / Devices

### Emergency lighting device 120V

Emergency lighting fitting, 120 V~ 50-60 Hz, Ni-Cd rechargeable battery, provided with FD 4W G5 fluorescent lamp and mounting frame for 6/7-module flush mounting boxes. To complete with 7-module cover plate



### Product Status

2 - Will be discontinued

### Minimum order quantity

1 NR

### Sheets, Manuals, Documentation

- [FI - Foglio istruzioni ZIS\\_49400246A0 \(772 kb\)](#)

## Technical data

- **Class group:** Luminaires
- **Class:** Emergency luminaire
- **Mounting method:** Built-in
- **Monitoring equipment:** None
- **With remote switch connection:** No
- **Power supply system:** Peripheral (individual battery)
- **Battery quality:** NiCd
- **Lamp type:** Fluorescent lamp
- **With light source:** Yes
- **Housing material:** Plastic
- **Housing colour:** White
- **Material cover:** Without cover
- **Voltage type:** AC
- **Nominal voltage:** 120,00 - 120,01 V
- **Degree of protection (IP):** IP40
- **Protection class:** II
- **Max. system power:** 4,00 W
- **Rated luminous flux according to IEC 62722-2-1:** 26
- **Width:** 203,40 mm
- **Height/depth:** 74,00 mm
- **Built-in width:** 203,40 mm
- **Built-in height/depth:** 47,10 mm

## Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352146648  
**Quantity** 1 NR  
**Dim.** 21.4x6.6x9.3 [cm]  
**Weight** 488.53 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).