



## PLANA: Emergency lighting device 120V

#### 14393

Wiring devices / Traditional wiring devices / PLANA / Devices

## **Emergency lighting device 120V**

Emergency lighting fitting,  $120 \text{ V} \sim 50\text{-}60 \text{ Hz}$ , Ni-Cd rechargeable battery, provided with FD 4W G5 fluorescent lamp and mounting frame for 6/7- module flush mounting boxes. To complete with 7-module cover plate



#### **Product Status**

2 - Will be discontinued

### Minimum order quantity

1 NR

#### Sheets, Manuals, Documentation

FI - Foglio istruzioni ZIS\_49400246A0 (772 kb)

## Technical data

Class group: Luminaires

Class: Emergency luminaire

Mounting method: Built-in

Monitoring equipment: None

With remote switch connection: No

**Power supply system**: Peripheral (individual battery)

**Battery quality**: NiCd

Lamp type: Fluorescent lamp

With light source: Yes

Housing material: Plastic

Housing colour: White

Material cover: Without cover

Voltage type: AC

**Nominal voltage**: 120,00 - 120,01 V

**Degree of protection (IP)**: IP40

■ Protection class: II

Max. system power: 4,00 W

Rated luminous flux according to IEC 62722-2-1: 26

**Width**: 203,40 mm

Height/depth: 74,00 mm

Built-in width: 203,40 mm

Built-in height/depth: 47,10 mm

## Certifications

- 00. CE Marking EU
- 37. Marking Morocco

- 43. UKCA mark Great Britain
- 99. WEEE Directive (download)

# **Packaging**



**Code** 8007352146648

Quantity 1 NR

**Dim.** 21.4x6.6x9.3 [cm]

**Weight** 488.53 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.