



PLANA: 1P+N C6 RCBO 120-230V 10mA white

14411.06

Wiring devices / Traditional wiring devices / PLANA / Devices

1P+N C6 RCBO 120-230V 10mA white

1P+N C 6 residual current breaker with overcurrent protection, supply voltage 120-230 V~ 50-60 Hz, $I_{\Delta n}$ 10 mA, breaking capacity 1500 A, white - 2 modules

Product Status

3 - Active


Minimum order quantity

5 NR


Sheets, Manuals, Documentation

- [Multilanguage instructions sheet \(688 kb\)](#)


Drawings



Space view



Backside view



3D View



Technical data

- **Class group:** Circuit breakers and fuses
- **Class:** Earth leakage circuit breaker
- **Number of poles (total):** 2
- **Number of protected poles:** 1
- **Rated voltage:** 230 V
- **Rated current:** 6 A
- **Rated fault current:** 6 A
- **Leakage current type:** A
- **Current limiting class:** 1
- **Rated short-circuit breaking capacity I_{cn} according to EN 61009-1:** 1.500,00 kA
- **Surge current capacity:** 1,50 kA
- **Voltage type:** AC
- **Frequency:** 50/60 Hz
- **Release characteristic:** C
- **Concurrently switching neutral conductor:** Yes
- **Overvoltage category:** 3
- **Built-in depth:** 38,00 mm
- **Flush-mounted installation:** Yes
- **Anti- nuisance tripping version:** No
- **Degree of protection (IP):** IP40

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352107915
Quantity 1 NR
Dim. 6x5.4x5.3 [cm]
Weight 97.13 [g]

Code 8007352107922
Quantity 5 NR
Dim. 17.2x13.1x6 [cm]
Weight 545.87 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).