IDEA: 1P 16AX 2-way switch luminous grey

16025

Wiring devices / Traditional wiring devices / IDEA / Devices

1P 16AX 2-way switch luminous grey

1P 16 AX 250 V~ 2-way switch, luminous, for signalling unit, grey. Provided without signalling unit. Max 200 W for self-ballasted lamps (IEC 60669-1:2017)

Product Status

3 - Active

Minimum order quantity

20 NR

Drawings



Space view



Backside view



3D View

Certifications

- **00. CE Marking - EU**
- **01. IMQ - Italy**
- **14. TSE - Turkey (download)**
- **15. CCC - China (download)**
- **19. NOM - Mexico**
- **20. IQC - Argentina**
- **35. RCM - Australia**
- **37. Marking - Morocco**
- **96. Electrotechnical expert (download)**
- **99. WEEE Directive (download)**

Technical data

Class group: Domestic switching devices

Class: Installation switch

Wiring system: Two-way switch

Operating method: Rocker/button

Assembly arrangement: Modular device for domestic switching devices

Number of modules (module system): 1

Push button switch: Yes

Number of rockers: 1

Mounting method: Flush-mounted

Type of fastening: Engage (snap)

With mounting plate: No

Material: Plastic

Material quality: Thermoplastic

Halogen free: Yes

Surface protection: Untreated

Surface finishing: Matt

Colour: Grey

RAL-number (similar): 7015

Label space/information surface: Yes

Lighting: Optional

Function lighting: Control and orientation

Type of lighting: LED exchangeable

Suitable for degree of protection (IP): IP40

Nominal voltage: 250 V

Rated current: 16,00 A

Monitoring contact: No

Connection type: Screwed terminal

Washing machine switch: No

Device width: 24,80 mm

Device height: 50,10 mm

Device depth: 36,50 mm

Built-in depth: 23,30 mm

Packaging

8007352078246

Qtà	1 NR
Dim	4.1x2.8x5.3 [cm]
Weight	30 [g]

8007352078253

Qtà	20 NR
Dim	21.4x11.6x6 [cm]
Weight	657.33 [g]

8007352641136

Qtà	200 NR
Dim	30.5x25.5x22.5 [cm]
Weight	7,240 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.