



IDEA: 2P+E French outlet +block-device red

16213.R

Wiring devices / Traditional wiring devices / IDEA / Devices

2P+E French outlet +block-device red

2P+E 16 A 250 V~ SICURY socket outlet, French standard, with locking device for the insertion of special purpose plugs, red - 2 modules. Provided with releasing device 01079

Product Status 2 - Will be discontinued

Minimum order quantity 20 NR



Technical data

- Class group: Domestic switching devices
- **Class**: Socket outlet
- Number of units: 1
- Number of modules (module system): 2
- Number of socket outlets switchable: 0
- Imprint/indication: None
- Connection type: Screwed terminal
- With hinged lid: No
- With enhanced contact protection: Yes
- Label space/information surface: Yes
- **Colour**: Red
- RAL-number (similar): 3001
- Metallic colour: No
- Transparent: No
- Lockable: Yes
- **Eject-mechanism**: No
- Insulated mounting: No
- With function lighting: No
- With orientation lighting: No
- **Over voltage protection**: No

Certifications

- 00. CE Marking EU
- 10. EAC Eurasian Customs Union

Packaging



Code	8007352031999
Quantity	1 NR
Dim.	5.1x4.3x5.3 [cm]
Weight	45.4 [g]

Code Quantity Dim. Weight

8007352032002 20 NR 26.9x11.6x9 [cm] 983.8 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Fault current protection: No
- With miniature fuse: No
- Mounting method: Flush-mounted
- Type of fastening: Snap mounting (engagement)
- Material: Plastic
- Material quality: Thermoplastic
- Halogen free: Yes
- Surface protection: Untreated
- Surface finishing: Matt
- With loop through function: No
- With on/off switch: No
- Rotated central insert: No
- Nominal current: 16 A
- Nominal voltage: 250 V
- Frequency: 50,00 60,00 HZ
- Suitable for degree of protection (IP): IP20
- Impact strength: Other
- Device width: 49,80 mm
- Device height: 50,10 mm
- Device depth: 35,50 mm
 - 37. Marking Morocco
 - 99. WEEE Directive (download)