



IDEA: Emergency lighting fitting 230V

16440

Wiring devices / Traditional wiring devices / IDEA / Devices

Emergency lighting fitting 230V

Emergency lighting fitting, $230 \text{ V} \sim 50\text{-}60 \text{ Hz}$, Ni-Cd rechargeable battery, provided with FD 4W G5 fluorescent lamp and mounting frame for 6/7-module flush mounting boxes. To complete with 6-module Classica or Rondò cover plates



Product Status

2 - Will be discontinued

Minimum order quantity

1 NR

Sheets, Manuals, Documentation

Multilanguage instructions sheet (135 kb)

Technical data

Class group: Luminaires

Class: Emergency luminaire

Mounting method: Built-in

Monitoring equipment: None

With remote switch connection: No

Power supply system: Peripheral (individual battery)

Battery quality: NiCd

Lamp type: Fluorescent lamp

With light source: YesHousing material: Plastic

Housing colour: Grey

Material cover: Without cover

Voltage type: AC

Nominal voltage: 230,00 - 230,01 V

Degree of protection (IP): IP40

Protection class: ||

• Max. system power: 4,00 W

Rated luminous flux according to IEC 62722-2-1: 26

Width: 192,40 mm

Height/depth: 57,70 mmBuilt-in width: 192,40 mm

Built-in height/depth: 46,50 mm

Certifications

- 00. CE Marking EU
- 10. EAC Eurasian Customs Union
- 17. ENEC 03 (IMQ) (download)
- 37. Marking Morocco

- 43. UKCA mark Great Britain
- 96. Electrotechnical expert (download)
- 99. WEEE Directive (download)

Packaging



21.4x6.6x9.3 [cm] Dim.

Weight 464.47 [g]

8007352099302 **Quantity** 1 NR

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.