



## IDEA: Connected roller shutter actuator white

---

### 16494.B

Wiring devices / View Wireless wiring devices / IDEA / Devices

#### Connected roller shutter actuator white

View Wireless electronic control for 1 roller shutter with slat orientation and change-over relay output for cosφ 0.6 motor 2 A 100-240 V~ 50/60 Hz, local or remote control, double IoT technology on Bluetooth 5.0 standard for the creation of View Wireless mesh system and on Zigbee 3.0 standard, 1 input for external push button to recall a scenario, favourite position recall function, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, white

- Configuration from View Wireless App for Bluetooth technology system and Amazon App for Zigbee technology
- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub
- Compatible with SmartThings hub



#### Product Status

3 - Active

#### Minimum order quantity

1 NR


## Sheets, Manuals, Documentation

- [Light multilanguage instructions sheet \(940 kb\)](#)
- [Foglio istruzioni Full \(508 kb\)](#)
- [Feuille d'instructions Full \(509 kb\)](#)
- [Hoja de instrucciones Full \(507 kb\)](#)
- [Full instructions sheet \(504 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(653 kb\)](#)
- [Anweisungsblatt Full \(776 kb\)](#)
- [Full \(575 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)


## Video

- [Creating-the-system](#)
- [Customisations](#)
- [Operation-in-Zigbee-mode](#)
- [Bluetooth-wifi-gateway](#)


## Drawings



Space view



Backside view



3D View

## Technical data

- **Class group:** Domestic switching devices
- **Class:** Push button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Model:** Group push button
- **Method of operation:** Push button
- **Number of rockers:** 2
- **Number of modules (module system):** 100
- **Number of poles:** 1
- **Nominal voltage:** 230 V
- **Rated current:** 2,00 A
- **With lighting:** Yes
- **With signal lamp:** Yes
- **Feedback-signal contact:** No
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Anti-bacterial treatment:** No
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** White
- **RAL-number (similar):** 9001
- **Transparent:** No
- **Label space/information surface:** Yes
- **Imprint:** Other
- **Device width:** 22,30 mm
- **Device height:** 49,00 mm
- **Device depth:** 46,40 mm

## Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 40. Bluetooth technology
- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352642997  
**Quantity** 1 NR  
**Dim.** 5.2x3.5x5.3 [cm]  
**Weight** 56.6 [g]



**Code** 8007352649507  
**Quantity** 60 NR  
**Dim.** 27x23x12.5 [cm]  
**Weight** 3,710 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).