



IDEA: MASTER dimmer 120V white

16559.1.120.B

Wiring devices / Traditional wiring devices / IDEA / Devices

MASTER dimmer 120V white

Universal dimmer 120 V~ 60 Hz for 40-400 W incandescent lamps, 40-300 VA electronic transformers, 10-200 W CFL lamps, 3-200 W LED lamps, for LED electronic power supply units, ON/OFF control and regulation by built-in push button or via NO peripheral push buttons, minimum brightness control, visible in darkness, white. Device not suitable for installation in Isoset enclosures

Product Status

3 - Active


Minimum order quantity

1 NR


Sheets, Manuals, Documentation

• Multilanguage instructions sheet (2498 kb)

Drawings



Space view



Backside view



Technical data

- Class group: Domestic switching devices
- Class: Dimmer
- Method of operation: Push button
- **Type of load**: Universal and LED Retrofit
- Applicable with button: Yes
- Applicable with movement sensor: No
- Applicable with presence indicator: No
- **Applicable with time switch/timer**: No
- Applicable with transmission button: No
- Applicable with infrared button: No
- Mounting method: Flush-mounted
- Type of fastening: Snapper mounting
- Material: Plastic
- Material quality: Thermoplastic
- Certifications
 - 00. CE Marking EU
 - 37. Marking Morocco

Packaging



8 0 0 7 3 5 2 5 7 5 9	930
Code 8007352575	936

 Code
 8007352575929

 Quantity
 1 NR

 Dim.
 5.1x4.3x5.3 [cm]

 Weight
 59.1 [g]

Code Quantity Dim. Weight

10 NR 26.9x11.6x4.9 [cm] 655.8 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Surface protection: Untreated
- Surface finishing: Matt
- Colour: White
- RAL-number (similar): 9001
- Transparent: No
- Suitable for degree of protection (IP): IP40
- Nominal voltage: 120,00 120,01 V
- Frequency: 60,00 60,01 HZ
- **Control voltage**: 120,00 120,01 V
- Connection type: Screwed terminal
- Device width: 24,80 mm
- Device height: 50,10 mm
- Device depth: 58,20 mm

99. WEEE Directive (download)