



IDEA: Univ.MASTER rotary-dimmer 230V grey

16603.1

Wiring devices / Traditional wiring devices / IDEA / Devices

Univ.MASTER rotary-dimmer 230V grey

Universal phase cutting dimmer 230 V~ 50 Hz, for 40-400 W incandescent lamps, 40-300 VA electronic transformers, 10-200 W CFL lamps, 3-200 W LED lamps, for LED phase cutting electronic power supply units, ON/OFF control with built-in push button or via NO peripheral push buttons, dimming with built-in rotary potentiometer, minimum brightness control, visible in darkness, grey. Device not suiTable for installation in Isoset enclosures

Product Status

3 - Active


Minimum order quantity

10 NR

Sheets, Manuals, Documentation

• Multilanguage instructions sheet (2356 kb)

Drawings







3D View

Space view

Backside view



Technical data

- Class group: Domestic switching devices
- Class: Dimmer
- Method of operation: Turn button
- Type of load: Universal and LED Retrofit
- Applicable with button: Yes
- Applicable with movement sensor: No
- Applicable with presence indicator: No
- Applicable with time switch/timer: No
- Applicable with transmission button: No
- Applicable with infrared button: No
- **Mounting method**: Flush-mounted
- Type of fastening: Snapper mounting
- Material: Plastic
- Material quality: Thermoplastic
- Certifications
 - 00. CE Marking EU
 - 37. Marking Morocco

Packaging



8	8 8 7 3 5 2 5 5 5 7

 Code
 8007352555754

 Quantity
 1 NR

 Dim.
 5.2x3.9x6.2 [cm]

 Weight
 57.7 [g]

Code Quantity Dim. Weight 8007352555761 10 NR 20.5x11.5x7 [cm] 641.5 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Surface protection: Untreated
- Surface finishing: Matt
- **Colour**: Grey
- RAL-number (similar): 9001
- Transparent: No
- Suitable for degree of protection (IP): IP40
- Nominal voltage: 230,00 230,01 V
- Frequency: 50,00 50,01 HZ
- **Control voltage**: 230,00 230,01 V
- Connection type: Screwed terminal
- Device width: 24,80 mm
- Device height: 50,10 mm
- Device depth: 60,40 mm
- 43. UKCA mark Great Britain
- 99. WEEE Directive (download)