



## IDEA: TV-RD-SAT single conn.male outlet 1dB w

### 17066.01.B

Wiring devices / Traditional wiring devices / IDEA / Devices

### TV-RD-SAT single conn.male outlet 1dB w

Coaxial TV-RD-SAT 5-2400 MHz socket outlet, single connection, with IEC 60169-2 male connector, connection attenuation 1 dB, white - reduced module. Allows the passage of d.c. current and control signals (24 V 500 mA max).

### Product Status


3 - Active

### Minimum order quantity


20 NR




### Drawings



Space view



Backside view



3D View

### Technical data

- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** End socket
- **Cover:** None
- **Tap loss at 860 MHz:** 0,10 dB
- **Tap loss at 2150 MHz:** 0,20 dB
- **Number of outlets:** 1
- **Suitable for remote power supply:** Yes
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** White
- **RAL-number (similar):** 9001
- **Material:** Plastic

## Certifications

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

## Packaging



8 007352 011557

**Code** 8007352011557  
**Quantity** 1 NR  
**Dim.** 4.1x2.8x5.3 [cm]  
**Weight** 41.2 [g]



8 007352 013841

**Code** 8007352013841  
**Quantity** 20 NR  
**Dim.** 21.4x11.6x6 [cm]  
**Weight** 881 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).