



ARKÉ: 2P+E 16A Universal+USB-C outlet grey

19210.USB

Wiring devices / Traditional wiring devices / ARKÉ / Devices

2P+E 16A Universal+USB-C outlet grey

- Device on 2 modules capable of simultaneously charging 2 devices, thanks to the universal socket outlet and the type C 3A USB socket outlet

Product Status

3 - Active


Minimum order quantity

1 NR


Sheets, Manuals, Documentation

- [Light multilanguage instructions sheet \(496 kb\)](#)
- [Full Multilanguage instructions sheet \(819 kb\)](#)


Drawings



Space view



Backside view



3D View



Gallery



Technical data

- **Class group:** Domestic switching devices
- **Class:** Socket outlet
- **Model:** Other
- **Number of active contacts (round):** 0
- **Number of active contacts (flat):** 0
- **With signal lamp:** No
- **Number of units:** 1
- **Number of modules (module system):** 2
- **Number of socket outlets switchable:** 0
- **Number of phases:** 2
- **Imprint/indication:** Other
- **Connection type:** Screwed terminal
- **With hinged lid:** No
- **With enhanced contact protection:** Yes
- **Label space/information surface:** No
- **Colour:** Grey
- **RAL-number (similar):** 7015
- **Metallic colour:** No
- **Transparent:** No
- **Lockable:** No
- **Eject-mechanism:** No
- **Insulated mounting:** Yes
- **With function lighting:** No
- **With orientation lighting:** No
- **Over voltage protection:** No
- **Fault current protection:** No
- **With miniature fuse:** No
- **Special power supply:** No special power supply
- **Mounting method:** Flush-mounted
- **Type of fastening:** Snap mounting (engagement)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Anti-bacterial treatment:** No
- **With loop through function:** Yes
- **With on/off switch:** No
- **Rotated central insert:** No
- **Nominal current:** 16 A
- **Nominal voltage:** 250 V
- **Frequency:** 50,00 - 60,00 HZ
- **Suitable for degree of protection (IP):** IP20
- **Device width:** 44,80 mm
- **Device height:** 49,00 mm
- **Device depth:** 52,00 mm
- **Min. depth of built-in installation box:** 48 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Amazon Alexa:** No
- **Compatible with Google Assistant:** No
- **IFTTT support available:** No
- **For heavy conditions according to VDE:** No


Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352707047
Quantity 1 NR
Dim. 6x5.4x5.3 [cm]
Weight 28.5 [g]



Code 8007352710092
Quantity 10 NR
Dim. 28.1x13.1x6 [cm]
Weight 358.4 [g]



Code 8007352710108
Quantity 120 NR
Dim. 38.5x29x30 [cm]
Weight 4,608 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).