



ARKÉ: 2P+E 16A P30 outlet+C16 RCBO Metal

19286.M

Wiring devices / Traditional wiring devices / ARKÉ / Devices

2P+E 16A P30 outlet+C16 RCBO Metal

2P+E 16 A 250 V~ SICURY socket outlet, Italian standard P30 (lateral and central earth contacts), interlocked with 1P+N C 16 residual current breaker with overcurrent protection, supply voltage 230 V~ 50 Hz, $I_{\Delta n}$ 10 mA, breaking capacity 3000 A, Metal - 4 modules

Product Status

3 - Active

Minimum order quantity

1 NR


Sheets, Manuals, Documentation

- [Multilanguage instructions sheet \(777 kb\)](#)


Video

- [Arké lives in your time](#)


Drawings




Space view



Backside view



3D View



Technical data

- **Class group:** Domestic switching devices
- **Class:** Socket outlet
- **Model:** Italian type P30
- **Number of units:** 2
- **Number of modules (module system):** 4
- **Number of socket outlets switchable:** 1
- **Imprint/indication:** None
- **Connection type:** Screwed terminal
- **With hinged lid:** No
- **With enhanced contact protection:** Yes
- **Label space/information surface:** Yes
- **Colour:** Aluminium
- **RAL-number (similar):** 9007
- **Metallic colour:** No
- **Transparent:** No
- **Lockable:** No
- **Eject-mechanism:** No
- **Insulated mounting:** No
- **With function lighting:** Yes
- **With orientation lighting:** No
- **Over voltage protection:** No
- **Fault current protection:** Yes
- **With miniature fuse:** No
- **Mounting method:** Flush-mounted
- **Type of fastening:** Snap mounting (engagement)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Surface protection:** Lacquered
- **Surface finishing:** Matt
- **With loop through function:** No
- **With on/off switch:** Yes
- **Rotated central insert:** No
- **Nominal current:** 16 A
- **Nominal voltage:** 230 V
- **Frequency:** 50,00 - 50,01 HZ
- **Rated fault current:** 10 mA
- **Suitable for degree of protection (IP):** IP20
- **Impact strength:** Other
- **Device width:** 44,80 mm
- **Device height:** 49,00 mm
- **Device depth:** 56,30 mm

Certifications

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 99. WEEE Directive ([download](#))

Packaging



Code	8007352600386
Quantity	1 NR
Dim.	14.2x6.7x5.9 [cm]
Weight	184.6 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).