



ARKÉ: KNX outdoor transponder reader Metal

19457.M

Smart systems&products / KNX / ARKÉ / Devices

KNX outdoor transponder reader Metal

Transponder card reader for installation outside rooms, KNX standard, 2 NO 4 A 24 V~ relay outputs, 2 inputs, power supply 12-24 V~ 50-60 Hz and 12-24 Vdc (SELV), Metal - 3 modules. Supplied without transponder card

Product Status

3 - Active

Minimum order quantity

1 NR


Sheets, Manuals, Documentation

- [Full Multilanguage instructions sheet \(1432 kb\)](#)
- [Light multilanguage instructions sheet \(713 kb\)](#)
- [Manuale installatore \(1126 kb\)](#)
- [Installer manual \(961 kb\)](#)


Video

- [Arké lives in your time](#)


Drawings




Space view



Backside view



3D View



Technical data

- **Class group:** Installation bus systems
- **Class:** Access control unit for bus system
- **Bus system KNX:** Yes
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** No
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Surface protection:** Lacquered
- **Surface finishing:** Matt
- **Colour:** Aluminium
- **RAL-number (similar):** 9007
- **Transparent:** No
- **With bus connection:** Yes

Certifications

- 00. CE Marking - EU ([download](#))
- 27. KNX ([download](#))
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352594852
Quantity 1 NR
Dim. 11.2x9.6x9.8 [cm]
Weight 147.2 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).