



ARKÉ: 16 A IoT connected actuator grey

19593

Wiring devices / View Wireless wiring devices / ARKÉ / Devices

16 A IoT connected actuator grey

View Wireless connected electronic control device with NO 16 A 100-240 V~ 50/60 Hz relay output, local control with push button or remote control, double technology with Bluetooth® wireless technology 5.0 standard for the realization of View Wireless mesh system and Zigbee 3.0 standard, function for measuring the instant power and load cut-off threshold, RGB LED visible in darkness with brightness control, 100-240 V 50/60 Hz power supply, grey

- Configuration from View Wireless App for Bluetooth technology system and Amazon App for Zigbee technology
- Compatible with Alexa, Google Home and IFTTT, using the dedicated gateway or Zigbee hub
- Compatible with SmartThings hub



Product Status

3 - Active

Minimum order quantity

1 NR


You may also be interested in



19597 - IoT connected gateway 2M grey



19203 - 2P+E 16A P17/11 outlet grey



03925 - Bluetooth Low Energy RF device


Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(1031 kb\)](#)
- [Foglio istruzioni Full \(550 kb\)](#)
- [Feuille d'instructions Full \(548 kb\)](#)
- [Hoja de instrucciones Full \(546 kb\)](#)
- [Full instructions sheet \(544 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(720 kb\)](#)
- [Anweisungsblatt Full \(547 kb\)](#)
- [Full \(610 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)

Video

- [Creating-the-system](#)
- [Customisations](#)
- [Operation-in-Zigbee-mode](#)
- [Bluetooth-wifi-gateway](#)


Drawings



Space view



Backside view



3D View

Gallery




Technical data

- **Class group:** Installation bus systems
- **Class:** Switch actuator for bus system
- **Bus system KNX:** No
- **Bus system KNX-RF (Radio Frequent):** No
- **Bus system radio frequent:** Yes
- **Bus system LON:** No
- **Bus system Powernet:** No
- **Other bus systems:** Other
- **Radio frequent bidirectional:** Yes
- **Mounting method:** Flush-mounted
- **Width in number of modular spacings:** 1
- **Local operation/hand operation:** Yes
- **With LED indication:** Yes
- **Max. number of switching contacts:** 1
- **Rated current:** 16 A
- **Rated operating voltage:** 100,00 - 240,00 V
- **Different phases connectable:** No
- **With bus connection:** Yes
- **Bus module detachable:** No
- **Modular expandability:** No

Certifications


- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 19. NOM - Mexico
- 29. QCERT - Colombia
- 37. Marking - Morocco
- 40. Bluetooth technology
- 42. Zigbee certified
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



8 007352 628427

Code 8007352628427
Quantity 1 NR
Dim. 6x5.4x5.2 [cm]
Weight 52 [g]



8 007352 628434

Code 8007352628434
Quantity 60 NR
Dim. 37.5x30x13.5 [cm]
Weight 3,310 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).