



EIKON: Univ.MASTER rotary-dimmer 230V white

20136.1.B

Wiring devices / Traditional wiring devices / EIKON / Devices

Univ.MASTER rotary-dimmer 230V white

Universal-dimmer 230 V~ 50 Hz, phase-cutting, for: 40-400 W incandescent lamps, 40-300 VAelectronic transfomers, 10-200 W CFL lamps, 3-200 W LED lamps and LED phase-cutting electronic transfomers, ON/OFF or built-in or from NO peripheral push buttons control, regulation by rotary potentiometer, MASTER function for 20137, minimum brightness regulation, visible in darkness, white. Not for Isoset enclosures

Product Status

3 - Active

Minimum order quantity

10 NR

Sheets, Manuals, Documentation

• Multilanguage instructions sheet (2356 kb)



Technical data

- Class group: Domestic switching devices
- Class: Dimmer
- Method of operation: Turn button
- Type of load: Universal and LED Retrofit
- Applicable with button: Yes
- Applicable with movement sensor: No
- Applicable with presence indicator: No
- Applicable with time switch/timer: No
- Applicable with transmission button: No
- Applicable with infrared button: No
- **Mounting method**: Flush-mounted
- Type of fastening: Snapper mounting
- Material: Plastic
- Material quality: Thermoplastic
- Certifications
 - 00. CE Marking EU
 - 31. TISI Thailand
 - 37. Marking Morocco

Packaging



Code	8007352555938
Quantity	1 NR
Dim.	5.2x3.9x6.2 [cm]
Weight	56.8 [g]



8007352555945 10 NR 20.5x11.5x7 [cm] 628.4 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Surface protection: Untreated
- Surface finishing: Matt
- **Colour**: White
- RAL-number (similar): 9016
- Transparent: No
- Suitable for degree of protection (IP): IP40
- Nominal voltage: 230,00 230,01 V
- Frequency: 50,00 50,01 HZ
- **Control voltage**: 230,00 230,01 V
- Connection type: Screwed terminal
- Device width: 22,30 mm
- Device height: 49,00 mm
- Device depth: 61,30 mm
- 43. UKCA mark Great Britain
- 92. RoHS UAE
- 99. WEEE Directive (download)