



# EIKON: Univ.MASTER rotary-dimmer 230V Next

#### 20136.1.N

Wiring devices / Traditional wiring devices / EIKON / Devices

#### **Univ.MASTER rotary-dimmer 230V Next**

Universal-dimmer 230 V $\sim$  50 Hz, phase-cutting, for: 40-400 W incandescent lamps, 40-300 VAelectronic transfomers, 10-200 W CFL lamps, 3-200 W LED lamps and LED phase-cutting electronic transfomers, ON/OFF or built-in or from NO peripheral push buttons control, regulation by rotary potentiometer, MASTER function for 20137, minimum brightness regulation, visible in darkness, Next. Not for Isoset enclosures



#### **Product Status**

3 - Active

### Minimum order quantity

10 NR

#### Sheets, Manuals, Documentation

Multilanguage instructions sheet (2356 kb)

## Technical data

Class group: Domestic switching devices

Class: Dimmer

Method of operation: Turn button

Type of load: Universal and LED Retrofit

Applicable with button: Yes

• Applicable with movement sensor: No

**Applicable with presence indicator**: No **Applicable with time switch/timer**: No

Applicable with transmission button, No

Applicable with transmission button: No
 Applicable with infrared button: No

Mounting method: Flush-mounted

Type of fastening: Snapper mounting

Material: Plastic

Material quality: Thermoplastic

Surface protection: Lacquered

Surface finishing: Matt

**Colour**: Silver

RAL-number (similar): 9022

**Transparent**: No

Suitable for degree of protection (IP): IP40

Nominal voltage: 230,00 - 230,01 V

**Frequency**: 50,00 - 50,01 HZ

Control voltage: 230,00 - 230,01 V
Connection type: Screwed terminal

**Device width**: 22,30 mm **Device height**: 49,00 mm **Device depth**: 61,30 mm

### Certifications

00. CE Marking - EU

31. TISI - Thailand

37. Marking - Morocco

43. UKCA mark - Great Britain

92. RoHS UAE

99. WEEE Directive (download)

## Packaging



Code 8007352555631 Quantity 1 NR

**Dim.** 5.2x3.9x6.2 [cm]

**Weight** 56.2 [g]

8 9 9 7 3 5 2 5 5 5 6 4 8

**Code** 8007352555648 **Quantity** 10 NR

**Dim.** 20.5x11.5x7 [cm]

**Weight** 625.8 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.