



EIKON: MASTER rotary dimmer 120V Next

20136.120.N

Wiring devices / Traditional wiring devices / EIKON / Devices

MASTER rotary dimmer 120V Next

Universal-dimmer, 120 V~ 60 Hz for: 40-500 W incandescent lamps, 40-300 VA electronic transformers, 10-200 W CFL lamps, 3-200 W LED lamps, LED electronic supply units, ON/OFF or built-in or from NO peripheral push buttons control, regulation by rotary potentiometer, MASTER function for 20137.120, minimum luminosity regulation, visible in darkness, Next. Not for lsoset enclosures

Product Status

2 - Will be discontinued


Minimum order quantity

1 NR

Sheets, Manuals, Documentation

FI - Foglio istruzioni ZIS_49400635A0 (2873 kb)

Drawings



Space view



Backside view





Technical data

- Class group: Domestic switching devices
- Class: Dimmer
- Method of operation: Turn button
- Type of load: Universal and LED Retrofit
- Applicable with button: Yes
- Applicable with movement sensor: No
- Applicable with presence indicator: No
- **Applicable with time switch/timer**: No
- Applicable with transmission button: No
- Applicable with infrared button: No
- Mounting method: Flush-mounted
- Type of fastening: Snapper mounting
- Material: Plastic
- Material quality: Thermoplastic
- Certifications
 - 19. NOM Mexico

Packaging



Code	8007352482111	(
Quantity	1 NR	(
Dim.	5.2x3.9x6.2 [cm]	
Weight	59.7 [g]	١

Code Quantity Dim. Weight

8007352482128 10 NR 20.5x11.5x7 [cm] 660 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Surface protection: Lacquered
- Surface finishing: Matt
- Colour: Silver
- RAL-number (similar): 9022
- Transparent: No
- Suitable for degree of protection (IP): IP40
- Nominal voltage: 120,00 120,01 V
- Frequency: 60,00 60,01 HZ
- **Control voltage**: 120,00 120,01 V
- Connection type: Screwed terminal
- Device width: 22,30 mm
- Device height: 49,00 mm
- Device depth: 61,30 mm

37. Marking - Morocco