



EIKON: MASTER dimmer 120-230V white

20148.B

Wiring devices / Traditional wiring devices / EIKON / Devices

MASTER dimmer 120-230V white

Dimmer, supply voltage 120-230 V \sim 50-60 Hz for: 40-500/40-800 W incandescent lamps and 40-300/40-500 VA ferromagnetic transformers, control and regulation with built-in or from peripheral NO push buttons, MASTER function, TRIAC technology, visible in darkness, white

Product Status

2 - Will be discontinued


Minimum order quantity

10 NR

Sheets, Manuals, Documentation

• Multilanguage instructions sheet (270 kb)

Drawings





Technical data

Class group: Domestic switching devices

Class: Dimmer

Method of operation: Push button

Type of load: Inductive load

Applicable with button: Yes

Applicable with movement sensor: No Applicable with presence indicator: No Applicable with time switch/timer: No Applicable with transmission button: No

Applicable with infrared button: No Mounting method: Flush-mounted Type of fastening: Snapper mounting

Material: Plastic

Certifications

00. CE Marking - EU

43. UKCA mark - Great Britain

Material quality: Thermoplastic

Surface protection: Untreated

Surface finishing: Matt

Colour: White

RAL-number (similar): 9016

Transparent: No

Suitable for degree of protection (IP): IP40

Nominal voltage: 120,00 - 230,00 V Frequency: 50,00 - 60,00 HZ

Control voltage: 120,00 - 230,00 V

Device width: 22,30 mm Device height: 49,00 mm Device depth: 52,40 mm

99. WEEE Directive (download)

Packaging



8007352316041 Code **Quantity** 1 NR

Dim. 5.1x4.3x5.3 [cm]

Weight 51.67 [g]



Code 8007352316058 Quantity 10 NR

Dim. 26.9x11.6x4.9 [cm]

Weight 583.07 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.