



## EIKON: IoT connected radar sensor 1M grey

---

**20179**

Wiring devices / View Wireless wiring devices / EIKON / Devices

### IoT connected radar sensor 1M grey

#### Product Status

3 - Active

#### Minimum order quantity


1 NR



#### Sheets, Manuals, Documentation

- [Light Multilanguage instructions sheet \(1346 kb\)](#)
- [Foglio istruzioni Full \(1138 kb\)](#)
- [Feuille d'instructions Full \(1139 kb\)](#)
- [Hoja de instrucciones Full \(1138 kb\)](#)
- [Full Instructions sheet \(1135 kb\)](#)
- [Φυλλάδιο οδηγιών Full \(1219 kb\)](#)
- [Anweisungsblatt Full \(1139 kb\)](#)
- [Full \(1219 kb\)](#)
- [Manuale app View Wireless \(15556 kb\)](#)
- [Manuel appli View Wireless \(37703 kb\)](#)
- [Manual app View Wireless \(37528 kb\)](#)
- [Manual View Wireless app \(37579 kb\)](#)
- [Εγχειρίδιο τεχνικού εγκατάστασης \(37781 kb\)](#)
- [Installationsanleitung View Wireless \(37508 kb\)](#)


## Drawings



Space view



Backside view



3D View

## Technical data

- **Class group:** Domestic switching devices
- **Class:** Movement sensor/presence detector complete
- **Model:** Movement sensor
- **Sensor type:** High frequency
- **With DALI interface:** No
- **Constant light control:** No
- **HVAC-control:** No
- **Forced switch on:** Yes
- **Forced switch off:** No
- **Animal zone:** Yes
- **Creep-under protection:** No
- **Networkable:** Yes
- **Scan angle:** 100
- **Staircase light controller:** No
- **Bridging switch:** No
- **Max. reach frontally:** 7 m
- **Suitable for wireless transmission:** Yes
- **Remote operation:** Yes
- **With remote control:** No
- **Response value sensitivity adjustable:** Yes
- **With signal unit:** Yes
- **Teach-function for response value luminosity:** No
- **Dim function with dimmer basic element:** No
- **Mounting method:** Flush-mounted
- **Suitable for ceiling mounting:** No
- **Connection type:** Screwed terminal
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Anti-bacterial treatment:** No
- **Colour:** Grey
- **RAL-number (similar):** 7024
- **Transparent:** No
- **Degree of protection (IP):** IP40
- **Voltage type:** AC
- **Frequency:** 50 - 60 HZ
- **Min. switch-on time:** 70 s
- **Switch-off delay:** 1.080 s
- **Detection angle horizontal:** 0 - 100
- **Max. switching power:** 960,00 W
- **Temperature:** 10 - 40 °C
- **Number of switching zones:** 1
- **Min. starting current:** 0 A
- **Substation input:** No
- **With alarm function:** Yes
- **Width:** 2.240,00 mm
- **Height:** 49,00 mm
- **Depth:** 4.950,00 mm
- **Diameter:** 0,00 mm
- **Built-in depth:** 4.000,00 mm
- **Built-in diameter:** 0,00 mm
- **Compatible with Apple HomeKit:** Yes
- **Compatible with Google Assistant:** Yes
- **Compatible with Amazon Alexa:** Yes

## Certifications

- 00. CE Marking - EU
- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 40. Bluetooth technology
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352709430  
**Quantity** 1 NR  
**Dim.** 6x5.4x5.2 [cm]  
**Weight** 46.6 [g]

**Code** 8007352709447  
**Quantity** 10 NR  
**Dim.** 28.1x13.1x6 [cm]  
**Weight** 543 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).