



# EIKON: 2P+E 16A P30 outlet red

### 20209.R

Wiring devices / Traditional wiring devices / EIKON / Devices

### 2P+E 16A P30 outlet red

2P+E 16 A 250 V~ SICURY socket outlet, Italian standard P30 (lateral and central earth contacts), for dedicated supply lines, red - 2 modules

### **Product Status**

3 - Active

**Minimum order quantity** 10 NR

Drawings



### Technical data

- Class group: Domestic switching devices
- Class: Socket outlet
- Model: Italian type P30
- Number of units: 1
- Number of modules (module system): 2
- Number of socket outlets switchable: 0
- Imprint/indication: None
- **Connection type**: Screwed terminal
- With hinged lid: No
- With enhanced contact protection: Yes
- Label space/information surface: Yes
- Colour: Red
- RAL-number (similar): 3001
- Metallic colour: No
- Transparent: No
- Lockable: No
- Eject-mechanism: No
- Insulated mounting: No
- With function lighting: No
- **With orientation lighting**: No
- Over voltage protection: No

# Certifications

- 00. CE Marking EU
- 01. IMQ Italy (download)
- 10. EAC Eurasian Customs Union

# Packaging





Code	8007352249578
Quantity	1 NR
Dim.	5.1x4.3x5.3 [cm]
Weight	48.27 [g]

Code Quantity Dim. Weight

8007352249585 10 NR 26.9x11.6x4.9 [cm] 546.27 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Fault current protection: No
- With miniature fuse: No
- Mounting method: Flush-mounted
- Type of fastening: Snap mounting (engagement)
- Material: Plastic
- Material quality: Thermoplastic
- Halogen free: Yes
- Surface protection: Untreated
- Surface finishing: Matt
- With loop through function: No
- With on/off switch: No
- Rotated central insert: No
- Nominal current: 16 A
- Nominal voltage: 250 V
- Frequency: 50,00 60,00 HZ
- Suitable for degree of protection (IP): IP20
- Impact strength: Other
- Device width: 44,80 mm
- Device height: 49,00 mm
- Device depth: 38,90 mm
  - 37. Marking Morocco
  - 99. WEEE Directive (download)