



EIKON: TV-RD-SAT single-conn.out.2outs grey

20302.01

Wiring devices / Traditional wiring devices / EIKON / Devices

TV-RD-SAT single-conn.out.2outs grey

Coaxial TV-RD-SAT 5-2400 MHz socket outlet, single connection, demix, 2 outputs with male (TV-RD) and female F-type (SAT) connectors, connection attenuation 1 dB, grey - 2 modules. Allows the passage of d.c. current and control signals (24 V 500 mA max) through the female connector

Product Status

3 - Active


Minimum order quantity

5 NR


Sheets, Manuals, Documentation

- [Multilanguage instructions sheet \(905 kb\)](#)


Drawings



Space view



Backside view



3D View



Technical data

- **Class group:** Antenna and satellite technique
- **Class:** Antenna socket box
- **Model:** TWIN end socket
- **Cover:** None
- **Tap loss at 860 MHz:** 1,00 dB
- **Tap loss at 2150 MHz:** 1,00 dB
- **Number of outlets:** 2
- **Suitable for remote power supply:** Yes
- **Type of fastening:** Snap mounting (engagement)
- **Colour:** Grey
- **RAL-number (similar):** 7024
- **Material:** Plastic

Certifications

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352400924
Quantity 1 NR
Dim. 5.1x4.3x5.3 [cm]
Weight 79 [g]



Code 8007352400948
Quantity 5 NR
Dim. 14.4x11.6x6 [cm]
Weight 447.8 [g]



Code 8007352640160
Quantity 60 NR
Dim. 36.5x33x13.5 [cm]
Weight 5,790 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).