



EIKON: 1P+N C6 120-230V CB Next

20405.06.N

Wiring devices / Traditional wiring devices / EIKON / Devices

1P+N C6 120-230V CB Next

1P+N C 6 circuit breaker, supply voltage 120-230 V~ 50-60 Hz, breaking capacity 1500 A, Next


Product Status

3 - Active


Minimum order quantity

5 NR


Drawings



Space view



Backside view



3D View



Technical data

- **Class group:** Circuit breakers and fuses
- **Class:** Miniature circuit breaker (MCB)
- **Built-in depth:** 38,00 mm
- **Release characteristic:** C
- **Number of poles (total):** 2
- **Number of protected poles:** 1
- **Rated current:** 6 A
- **Rated voltage:** 230 V
- **Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V:** 1,50 kA
- **Voltage type:** AC
- **Frequency:** 50 - 60 HZ
- **Current limiting class:** 1
- **Concurrently switching neutral conductor:** Yes
- **Over voltage category:** 3
- **Width in number of modular spacings:** 1
- **Degree of protection (IP):** IP40

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



8 007352286344

Code 8007352286344
Quantity 1 NR
Dim. 6x2.8x5.3 [cm]
Weight 55 [g]



8 007352286351

Code 8007352286351
Quantity 5 NR
Dim. 14.2x6.7x5.9 [cm]
Weight 305.47 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).