



# EIKON: Round plate 2MBS Bright anthracite

#### 20677.C12

Wiring devices / Traditional wiring devices / EIKON / Cover plates

#### Round plate 2MBS Bright anthracite

2-module Round cover plate for British standard, Bright varnished metal and chromed frame, metallic anthracite

#### **Product Status**

2 - Will be discontinued

#### Minimum order quantity


1 NR

### You may also be interested in



20607 - Frame 2M BS

### Drawings



Space view



Backside view



3D View



### Technical data

- Class group: Domestic switching devices
- Class: Cover frame for domestic switching devices
- Number of units: 2
- Mounting direction: Horizontal and vertical
- Number of units horizontal: 2
- Number of units vertical: 1
- Number of modules horizontal (module system): 2
- Number of modules vertical (module system): 1
- With mounting grid: Yes
- Suitable for subfloor installation duct box: Yes
- Suitable for wall duct: Yes
- Suitable for built-in installation: Yes
- Label space/information surface: Yes
- Material: Metal
- Material quality: Other

### Certifications

08. ASTA - UK

### Packaging





 Code
 8007352480742

 Quantity
 1 NR

 Dim.
 9.7x9.7x1.7 [cm]

 Weight
 98.4 [g]

Code Quantity Dim. Weight 8007352480759 5 NR 10.3x9.4x10.5 [cm] 535.2 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported.Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed.For the terms of use of the information on the product info sheet see Conditions of Use.

- Halogen free: Yes
- Surface protection: Lacquered
- Surface finishing: Glossy
- **Colour**: Anthracite
- RAL-number (similar): 7022
- Transparent: No
- With hinged lid: No
- Degree of protection (IP): IP00
- Type of fastening: Clamp mounting
- **Width**: 95,00 mm
- Height: 95,00 mm
- **Depth**: 9,00 mm
- Built-in width: 95,00 mm
- Built-in height: 95,00 mm
- **Diameter bore hole (opening)**: 0 mm