



LINEA: 1P 10AX 1-way switch mechanism

30000

Wiring devices / Traditional wiring devices / LINEA / Devices

1P 10AX 1-way switch mechanism

1P 10 AX 250 V~ lightable 1-way switch mechanism, to be completed with 1-module button. Max 100 W for lamps with built-in power supply unit (IEC 60669-1:2017)

Product Status

3 - Active

Minimum order quantity

50 NR




You may also be interested in



31000S.B - White lower 1M path light button



31000S.G - Black lower 1M path light button



31000S.C - Lower 1M path light button Canvas




31000A.B - Axial button 1M white



31000A.G - Axial button 1M black



31000A.C - Axial button 1M canvas



31000.B - Button 1M aligned white



31000.G - Button 1M aligned 1M black




31000.C - Button 1M aligned Canvas




00943.W - Linea 110-250V white LED unit


Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** Off switch 1-pole
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 1
- **Push button switch:** Yes
- **Number of rockers:** 1
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Anti-bacterial treatment:** No
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Black
- **RAL-number (similar):** 7021
- **Label space/information surface:** No
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 V
- **Rated current:** 10,00 A
- **Switching current for fluorescent lamps:** 10
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Heating switch:** No
- **Washing machine switch:** No
- **Device width:** 22,30 mm
- **Device height:** 49,50 mm
- **Device depth:** 28,90 mm
- **Built-in depth:** 31,80 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 13. SNI - Indonesia
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352674882
Quantity 1 NR
Dim. 4.6x2.7x5.6 [cm]
Weight 27.08 [g]



Code 8007352674899
Quantity 50 NR
Dim. 23.7x14.8x12.8 [cm]
Weight 1,495 [g]



Code 8007352674905
Quantity 300 NR
Dim. 45.5x27x27 [cm]
Weight 9,400 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).