



LINEA: 1P 10AX 2M axial reversing switch mech.

30012.2

Wiring devices / Traditional wiring devices / LINEA / Devices

1P 10AX 2M axial reversing switch mech.

1P 10 AX 250 V~ lightable reversing switch mechanism, to be completed with 2-module button - 2 modules. Max 100 W for lamps with built-in power supply unit (IEC 60669-1:2017)

Product Status


3 - Active

Minimum order quantity

20 NR




You may also be interested in



3100S.2B - Lower 2M path
light button white



3100S.2G - Lower 2M path
light button black




3100S.2C - Lower 2M path
light button canvas




3100A.2B - Axial button 2M
white



3100A.2G - Axial button 2M
black



3100A.2C - Axial button 2M
Canvas



31000.2B - Button 2M white



31000.2G - Button 2M black




31000.2C - Button 2M
Canvas




00943.W - Linea 110-250V
white LED unit


Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** Alternating-/alternating switch
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 2
- **Push button switch:** No
- **Number of rockers:** 1
- **Mounting method:** Flush-mounted
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Anti-bacterial treatment:** No
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Colour:** Black
- **RAL-number (similar):** 7021
- **Label space/information surface:** No
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Impact strength:** Other
- **Nominal voltage:** 250 V
- **Rated current:** 10,00 A
- **Switching current for fluorescent lamps:** 10
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Heating switch:** No
- **Washing machine switch:** No
- **Device width:** 44,70 mm
- **Device height:** 49,10 mm
- **Device depth:** 39,70 mm
- **Built-in depth:** 36,00 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Google Assistant:** No
- **Compatible with Amazon Alexa:** No
- **IFTTT support available:** No

Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352723153
Quantity 1 NR
Dim. 5.2x4.3x5.6 [cm]
Weight 43.44 [g]



Code 8007352723160
Quantity 20 NR
Dim. 23x11x12.4 [cm]
Weight 964.9 [g]



Code 8007352723177
Quantity 120 NR
Dim. 35x25x27.5 [cm]
Weight 6,125.4 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).