



LINEA: 2P+E 16A German SICURY outlet+cover canv

30208.CC

Wiring devices / Traditional wiring devices / LINEA / Devices

2P+E 16A German SICURY outlet+cover canv

SICURY 2P+T 16 A 250 V~ socket outlet, German standard with cover, lightable, canvas - 2 modules


Product Status

3 - Active

Minimum order quantity

10 NR


Drawings



Space view



Backside view



3D View



Technical data

- **Class group:** Domestic switching devices
- **Class:** Socket outlet
- **Model:** Socket outlet CEE 7/3 (type F)
- **Concurrently switching neutral conductor:** No
- **Protective contact:** Earthing clips
- **Number of active contacts (round):** 2
- **Number of active contacts (flat):** 0
- **Number of active contacts (square):** 0
- **With signal lamp:** No
- **Number of ports USB-A:** 0
- **Number of ports USB-C:** 0
- **Max. current rating of USB power supply:** 0 A
- **Number of units:** 1
- **Number of modules (module system):** 2
- **Number of socket outlets switchable:** 0
- **Number of phases:** 1
- **Imprint/indication:** None
- **Connection type:** Screwed terminal
- **With hinged lid:** Yes
- **With enhanced contact protection:** Yes
- **Label space/information surface:** No
- **Colour:** Beige
- **RAL-number (similar):** 7032
- **Metallic colour:** No
- **Transparent:** No
- **Lockable:** No
- **Eject-mechanism:** No
- **Insulated mounting:** Yes
- **With function lighting:** Yes
- **With orientation lighting:** No
- **Over voltage protection:** No
- **Fault current protection:** No
- **With miniature fuse:** No
- **Special power supply:** No special power supply
- **Mounting method:** Flush-mounted
- **Type of fastening:** Snap mounting (engagement)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Anti-bacterial treatment:** No
- **With loop through function:** Yes
- **Number of loop throughs:** 1
- **With on/off switch:** No
- **Colour of switch operator:** Other
- **Rotated central insert:** No
- **Nominal current:** 16 A
- **Nominal voltage:** 250 V
- **Frequency:** 50,00 - 60,00 HZ
- **Rated fault current:** 0 mA
- **Suitable for degree of protection (IP):** IP20
- **Impact strength:** Other
- **Device width:** 44,70 mm
- **Device height:** 52,80 mm
- **Device depth:** 42,70 mm
- **Min. depth of built-in installation box:** 38 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Amazon Alexa:** No
- **Compatible with Google Assistant:** No
- **IFTTT support available:** No
- **With Wi-Fi signal repeater:** No
- **With built-in bluetooth speaker:** No
- **For heavy conditions according to VDE:** No
- **Compliant with UK Building Regulations Part M:** No

Certifications

- 00. CE Marking - EU
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



Code 8007352744783
Quantity 1 NR
Dim. 5.6x4.7x5 [cm]
Weight 54.8 [g]

Code 8007352744790
Quantity 10 NR
Dim. 25.1x12.5x6 [cm]
Weight 622 [g]

Code 8007352744806
Quantity 140 NR
Dim. 45.5x27x27 [cm]
Weight 9,124 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).