



## LINEA: 2P+E 16A Universal outlet canvas

### 30210.C

Wiring devices / Traditional wiring devices / LINEA / Devices

### 2P+E 16A Universal outlet canvas

SICURY 2P+T 16 A 250 V~ universal socket outlet, Italian standard P40, canvas - 2 modules


### Product Status

3 - Active

### Minimum order quantity

20 NR


## Drawings



Space view



Backside view



3D View



## Technical data

- **Class group:** Domestic switching devices
- **Class:** Socket outlet
- **Model:** Other
- **Number of active contacts (round):** 0
- **Number of active contacts (flat):** 0
- **With signal lamp:** No
- **Number of units:** 1
- **Number of modules (module system):** 2
- **Number of socket outlets switchable:** 0
- **Number of phases:** 1
- **Imprint/indication:** Other
- **Connection type:** Screwed terminal
- **With hinged lid:** No
- **With enhanced contact protection:** Yes
- **Label space/information surface:** No
- **Colour:** Beige
- **RAL-number (similar):** 7032
- **Metallic colour:** No
- **Transparent:** No
- **Lockable:** No
- **Eject-mechanism:** No
- **Insulated mounting:** No
- **With function lighting:** No
- **With orientation lighting:** No
- **Over voltage protection:** No
- **Fault current protection:** No
- **With miniature fuse:** No
- **Special power supply:** No special power supply
- **Mounting method:** Flush-mounted
- **Type of fastening:** Snap mounting (engagement)
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Matt
- **Anti-bacterial treatment:** No
- **With loop through function:** No
- **With on/off switch:** No
- **Rotated central insert:** No
- **Nominal current:** 16 A
- **Nominal voltage:** 250 V
- **Frequency:** 50,00 - 60,00 HZ
- **Rated fault current:** 0 mA
- **Suitable for degree of protection (IP):** IP20
- **Device width:** 44,80 mm
- **Device height:** 52,80 mm
- **Device depth:** 36,10 mm
- **Compatible with Apple HomeKit:** No
- **Compatible with Amazon Alexa:** No
- **Compatible with Google Assistant:** No
- **IFTTT support available:** No
- **For heavy conditions according to VDE:** No


## Certifications

- 00. CE Marking - EU
- 03. CSV-IMQ - Italy ([download](#))
- 10. EAC Eurasian Customs Union
- 37. Marking - Morocco
- 50. Product Environm. Profile
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

# Packaging



**Code** 8007352686267  
**Quantity** 1 NR  
**Dim.** 5.2x4.3x5.6 [cm]  
**Weight** 48.8 [g]



**Code** 8007352686274  
**Quantity** 20 NR  
**Dim.** 23x11x12.4 [cm]  
**Weight** 1,070.2 [g]



**Code** 8007352686281  
**Quantity** 120 NR  
**Dim.** 35x25x27.5 [cm]  
**Weight** 6,788 [g]



**Code** 8007352750043  
**Quantity** 3,240 NR  
**Dim.** 120x80x105 [cm]  
**Weight** 183,254.4 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).