



### LINEA: Two 2P+E 15A USA outlet with GFCI black

#### 30296.G

Wiring devices / Traditional wiring devices / LINEA / Devices

#### Two 2P+E 15A USA outlet with GFCI black

Two 2P+T 15 A 125 V $\sim$  60 Hz American standard socket outlets with Ground Fault Circuit Interrupter (GFCI), device complete with mounting frame, to be completed with 3-module cover plate, black

# SPIGLIZING SYL BINDS SECULIAN SYLDEN SECULIAN SYLD

#### **Product Status**

3 - Active


#### Minimum order quantity

5 NR


#### Sheets, Manuals, Documentation

• Hoja de instrucciones multilingüe (1248 kb)

## Drawings







3D View

#### Technical data

Class group: Domestic switching devices

Class: Socket outlet

Number of active contacts (round): 0

Number of active contacts (flat): 0

Number of active contacts (square): 0

With signal lamp: No

Number of ports USB-A: 0

Number of ports USB-C: 0

Number of units: 1

Number of modules (module system): 3

Number of socket outlets switchable: 0

Number of phases: 1 Imprint/indication: None

**Connection type**: Screwed terminal

With hinged lid: No

With enhanced contact protection: No

**Label space/information surface**: Yes

Colour: Black

RAL-number (similar): 7021

Transparent: No Lockable: No

**Eject-mechanism**: No **Insulated mounting**: No

• With function lighting: No

• With orientation lighting: No

• Over voltage protection: No

• Fault current protection: Yes

With miniature fuse: No

Special power supply: No special power supply

Mounting method: Flush-mounted

Type of fastening: Mounting with screw

Material: Plastic

Material quality: Thermoplastic

**Halogen free**: Yes

Surface protection: Untreated

Surface finishing: Matt

Anti-bacterial treatment: No

With loop through function: No

With on/off switch: No

Rotated central insert: No

Nominal voltage: 125 V

Nominal voltage: 125 V Frequency: 60,00 - 60,01 HZ

Rated fault current: 6 mA

Suitable for degree of protection (IP): IP20

Impact strength: Other

**Device width**: 116,80 mm

• Device height: 79,00 mm

Device depth: 39,30 mm

• Compatible with Apple HomeKit: No

• Compatible with Amazon Alexa: No

Compatible with Google Assistant: No

IFTTT support available: No

With Wi-Fi signal repeater: No

With built-in bluetooth speaker: No

For heavy conditions according to VDE: No

## Certifications

29. QCERT - Colombia (download)

99. WEEE Directive (download)

## **Packaging**



Code Quantity Dim. Weight

8007352737907 1 NR 8x5x12.2 [cm]

148 [g]



Code Quantity

8007352737914

Dim. Weight 5 NR 26x13x8.7 [cm] 826.2 [g]

# Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see Conditions of Use.