



LINEA: Auxiliary emergency LED lamp 1M

30398

Wiring devices / Traditional wiring devices / LINEA / Devices

Auxiliary emergency LED lamp 1M

Auxiliary emergency lamp and controllable step marker lamp, high efficiency LEDs 100-240 V~ 50/60 Hz, can also be used as a courtesy light or a step marker lamp controlled by an external 1-way switch, non-replaceable rechargeable Li-ion battery, range of 2.5 hours, neutral

Product Status

3 - Active

Minimum order quantity


1 NR

Sheets, Manuals, Documentation

- [Light multilanguage instructions sheet \(545 kb\)](#)
- [Full multilanguage instructions sheet \(1135 kb\)](#)




Drawings



Space view



Backside view



3D View

Technical data

- **Class group:** Luminaires
- **Class:** Emergency luminaire
- **Mounting method:** Built-in
- **Function:** Escape route lighting
- **Suitable for labelling type:** Other
- **With pictogram:** No
- **Monitoring equipment:** None
- **With remote switch connection:** Yes
- **With remote control:** No
- **Power supply system:** Peripheral (individual battery)
- **Battery quality:** Lithium-ions
- **Lamp type:** LED not exchangeable
- **With light source:** Yes
- **Suitable for number of light sources:** 1
- **Lamp holder:** Other
- **Number of lighting heads:** 1
- **Housing material:** Plastic
- **Housing colour:** Colourless
- **Material cover:** Without cover
- **Voltage type:** AC
- **Nominal voltage:** 100,00 - 240,00 V
- **Type of control gear:** Not required
- **Exchangeable control gear:** No
- **Light distributor:** Other
- **Degree of protection (IP):** IP40
- **Degree of protection (NEMA):** Other
- **Protection class:** II
- **Max. system power:** 1,00 W
- **Nominal operation time:** 250,00 - 251,00 h
- **Width:** 22,20 mm
- **Height/depth:** 44,30 mm
- **Length:** 52,80 mm
- **Outer diameter:** 0 mm
- **Built-in width:** 22,20 mm
- **Built-in height/depth:** 38,60 mm
- **Built-in length:** 52,80 mm
- **Built-in diameter:** 0 mm
- **Type of wiring:** Ending
- **Number of poles:** 0
- **Conductor cross section:** 250
- **Connection type:** Screw connection

Certifications

- 00. CE Marking - EU
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

Packaging



8 007352704817

Code 8007352704817
Quantity 1 NR
Dim. 6x5.4x5.2 [cm]
Weight 43.2 [g]



8 007352704824

Code 8007352704824
Quantity 10 NR
Dim. 23.5x12.5x6.5 [cm]
Weight 510.2 [g]



8 007352713307

Code 8007352713307
Quantity 90 NR
Dim. 37.5x30x21 [cm]
Weight 5,000 [g]

Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).